

HS 8065DV

Hold Baggage & Freight X-Ray Machine



HISSCO

'THE HS 8065DV **EVO2**, For Hold Baggage and Freight Screening Requirements'



The **HS 8065DV (Dual View) EVO2** is an ideal solution for hold baggage and freight screening. With a tunnel size of 810mm x 660mm (31"x26") and dual-view imaging technology, it integrates easily into existing screening facilities. Its low conveyor design makes it highly versatile for oversized baggage, suitcases, parcels and more. Designed for high-transit environments such as train stations, hotels, airports, government facilities and others, the **HS 8065DV EVO2** delivers reliable performance across a wide range of screening applications.

The all-new **HS 8065DV EVO2** is highly regarded for its versatility and exceptional performance in the field. Now featuring industry-leading optional enhancements—including increased belt speeds up to 0.5 m/s, a touchscreen interface, **(AI) Assisted Imaging™**, and built-in item recognition training software—the **HS 8065DV EVO2** is setting a new standard in next-generation screening technology.

SPECIAL FEATURES

- 5 Years Parts Inclusive Warranty Only
- CIRTIS (Computer Item Recognition Training Software)
- Dual-energy high-definition detectors
- Compact design
- Self Diagnostics
- Organic / inorganic stripping (Material Discrimination)
- Automatic threat and density alert
- Network ready
- Image archiving

ADDITIONAL EXTRAS

- TIP –Threat Image Projection
- AI (Assisted Imaging)™ Item Recognition
- Roller tables (entry/exit) built to any length
- UPS (Uninterrupted Power Supply)
- Touch Screen Interface 21" Monitor
- Tunnel Guards
- Extended Belt Speed to 0.50 M/S



'THE HS 8065DV **VO2**, For Hold Baggage and Freight Screening Requirements'

SPECIFICATIONS

GENERAL

Construction:	Steel based
Tunnel Size:	31" (W) x 26" (H)
Length / Width / Height (in)	110" (L) 58" (W) x 56" (H)
	2205 lbs (uncrated)
	2645 lbs (crated)
Conveyor Height:	11.81"
Conveyor Speed:	0.22 meters per second
Maximum Conveyor Load:	440 lbs (evenly distributed)
System Noise Level:	<55 dB

PERFORMANCE INDEX *

Penetration:	36 mm Steel (guaranteed)
	38 mm Steel (typical)
Resolution (wire gauge):	40 AWG (guaranteed)
	42 AWG (typical)

X-RAY GENERATOR

Tube Voltage:	100 - 160 kV (adjustable)
	sealed oil bath
Tube Current:	0.3 - 1.2mA (adjustable)
Cooling / Duty Cycle:	Sealed oil cooling / 100%
Beam Launch Angle:	(1) Vertically Downward and (2) Horizontal

OPERATIONAL INDEX

Storage Temp/Humidity:	-20°C to 50°C
	10% - 95% non-condensing
Working Temp/Humidity:	0°C to 45°C
	10% - 95% non-condensing
Working Voltage:	AC 110V (± to 10%)
	50 Hz / 60 Hz ± 3 Hz
Power:	0.5 kVA
Leakage:	<0.5 µ Sv / H
Dose Per Inspection:	<1.5 µ Sv (typical)
Duty Cycle:	100% (no burn in necessary)

IMAGING

- Image resolution: 1280 x 1024 x 24 bits
- Zoom 2x - 64x (dynamic, smooth and continuous)
- Full screen zoom (one click)
- High, low penetration
- Organic / inorganic stripping
- Picture Pure screening technology
- Super edge enhancement capability
- Threat Image Projection Library (TIP)
- Operator assist (OA), automatic threat and density alert
- High Organic Mass Alert (HOMA)
- Automatic 100x screen image recall (last in first out)
- Dual-energy technology
- Color, black, white, inverse display

IMAGE RECALL

- 500,000 Images storage capacity (standard)
- Image conversion and export to jpg, png and bmp
- Image search and simulated playback
- Printer Ready

ADDITIONAL FEATURES

- 2 x 21" High resolution touch Screen Interface
- AI (Assisted Imaging)™ Item Recognition
- Input / Exit Rollers to any length required
- Multi language support
- Network capable
- CIRTIS (Computer Item Recognition Training Software)
- 5 Years Parts Inclusive Warranty Only
- Extended Belt Speed to 0.50 Meters Per Second

COMPLIANCE STANDARDS

- Complies with film safety ISO 1600 / 33 DIN high speed photographic film
- All equipment is CE (Europe) certified and manufactured to ISO 9001:2015 TUV standards, FDA 21CFR- Part 1003/1004 approved for use in the USA.
- Radiation safety: Meets all applicable laws and regulations with respect to X-ray emitting devices, with directives, 2014/30/EC, 2014/35/EC, 2006/42/EC, FDA 21CFR, SAPHRA.
- Proprietary quality management test piece: Steel step Wedge, CU wires, Shims, Organic Inorganic, Belt speed 0.20 m/s.

*Approximate Values (Adjustable)

